

# Certificate of Approval

This certificate confirms that the company below complies with the following standard(s):

Company Name	<b>Mercury Glass</b>	Client ID	<b>107317</b>
Company Other Name	<b>General Glass Supplies Pty Ltd</b>	Type of Certification	<b>Product Certification; System 5</b>
Certification Standard	<b>AS/NZS 2208-1996 : Safety glazing materials in buildings including Amendment 1</b>		
Scheme	<b>Global-Mark Product Conformance Scheme</b>		
Certification Review Date	<b>24/11/2020</b>	Certification Expiry Date	<b>7/07/2024</b>
Certificate Issue Date	<b>24/11/2020</b>	Certificate Last Update Date	<b>16/02/2021</b>

**APPROVED COMPANY/SITE ADDRESS(ES):**

**391 Bradman Street Acacia Ridge QLD 4110 Australia**

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate of Approval remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to [www.jas-anz.org/register](http://www.jas-anz.org/register) for verification.



**Certification Manager**

Unique Certificate Code: **39F117EDA53F944ECA258670006AB0C6**

Global-Mark Pty Ltd, 407, 32 Delhi Road, North Ryde NSW 2113, Australia - Copyright 2005



Global-Mark.com.au®



[WWW.JAS-ANZ.ORG/REGISTER](http://WWW.JAS-ANZ.ORG/REGISTER)

**Model(s) on which the Global-Mark logo may be applied by the certificate holder as a declaration of compliance by the certificate holder:**

*In placing the authorised mark on the product, the certificate holder makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. In issuing this Certificate of Approval Global-Mark has relied on the expertise of external bodies (laboratories, and technical experts).*

Model Identification	Model Name	Brand Name	Product Description/Attributes	Date Approved
Toughened 1	Toughened	Mercury Glass	Flat-Patterned ;Toughened; Thickness: 4-4; Colours: Clear; Patterns: A; Coatings: cathedral,satinlite, spotswood; Max size: 2440mm x 2200mm	24/11/2020
Toughened 2	Toughened	Mercury Glass	Flat-Patterned ;Toughened; Thickness: 5-8; Colours: Clear, Blue, Bronze, Green, Grey, Low-iron,; Patterns: A; Coatings: cathedral,satinlite, spotswood, Reed; Max size: 2350mm x 3550mm	24/11/2020
Toughened 3	Toughened	Mercury Glass	Flat-Patterned ;Toughened; Thickness: 5-6; Colours: Clear; Patterns: A; Coatings: cathedral,satinlite, spotswood; Max size: 2440mm x 5000mm	24/11/2020
Toughened 4	Toughened	Mercury Glass	Flat-Plain ;Toughened; Thickness: 5-8; Colours: Clear, Grey; Patterns: A; Coatings: NA; Max size: 2440mm x 5000mm	24/11/2020
Toughened 5	Toughened	Mercury Glass	Flat-Plain ;Toughened; Thickness: 5-12; Colours: Clear, Blue, Bronze, Green, Grey, Low-iron,; Patterns: A; Coatings: NA; Max size: 2350mm x 3550mm	24/11/2020
Toughened 6	Toughened	Mercury Glass	Flat-Plain ;Toughened; Thickness: 4-4; Colours: Clear, Blue, Bronze, Green, Grey, Low-iron; Patterns: A; Coatings: NA; Max size: 2440mm x 2200mm	24/11/2020
Toughened 7	Toughened	Mercury Glass	Flat-Plain ;Toughened; Thickness: 5-12; Colours: Clear, Blue, Bronze, Green, Grey, Low-iron; Patterns: A; Coatings: NA; Max size: 2440mm x 5000mm	24/11/2020
Toughened 8	Toughened	Mercury Glass	Flat-Plain ;Toughened; Thickness: 4-4; Colours: Clear, Grey; Patterns: A; Coatings: NA; Max size: 2440mm x 2200mm	24/11/2020
Laminated 1	EVA float laminated	Mercury Glass	Glass thickness from 8-24mm. Interlayer thickness:0.38, 0.76. Max size:3660*2440	16/02/2021
Laminated 2	EVA interlayer toughened laminated	Mercury Glass	Glass thickness from 8-24mm. Interlayer thickness:0.76mm ; 1.52mm, 2.28mm, 3.04mm Max size:3660*2440	16/02/2021
Laminated 3	SentryGlas interlayer laminated	Mercury Glass	Glass thickness from 8-24mm. Interlayer thickness:0.76mm ; 1.52mm, 2.28mm, 3.04mm Max size:3660*2440	16/02/2021

Comments:

End of the document



**Certification Manager**

